- (v) A limited rating for a manufacturer issued for the appliance in accordance with §145.101(b)(4) of this chapter; or
- (3) A certificated mechanic with an airframe rating (static pressure system tests and inspections only).
- (c) Altimeter and altitude reporting equipment approved under Technical Standard Orders are considered to be tested and inspected as of the date of their manufacture.
- (d) No person may operate an airplane, or helicopter, in controlled airspace under IFR at an altitude above the maximum altitude at which all altimeters and the automatic altitude reporting system of that airplane, or helicopter, have been tested.

EFFECTIVE DATE NOTE: At 66 FR 41116, Aug. 6, 2001, §91.411 was amended by removing paragraph (b)(2)(v), effective Apr. 6, 2003.

§91.413 ATC transponder tests and inspections.

- (a) No persons may use an ATC transponder that is specified in 91.215(a), 121.345(c), or §135.143(c) of this chapter unless, within the preceding 24 calendar months, the ATC transponder has been tested and inspected and found to comply with appendix F of part 43 of this chapter; and
- (b) Following any installation or maintenance on an ATC transponder where data correspondence error could be introduced, the integrated system has been tested, inspected, and found to comply with paragraph (c), appendix E, of part 43 of this chapter.
- (c) The tests and inspections specified in this section must be conducted by—
- (1) A certificated repair station properly equipped to perform those functions and holding—
 - (i) A radio rating, Class III;
- (ii) A limited radio rating appropriate to the make and model transponder to be tested;
- (iii) A limited rating appropriate to the test to be performed;
- (iv) A limited rating for a manufacturer issued for the transponder in accordance with §145.101(b)(4) of this chapter; or
- (2) A holder of a continuous airworthiness maintenance program as

- provided in part 121 or §135.411(a)(2) of this chapter; or
- (3) The manufacturer of the aircraft on which the transponder to be tested is installed, if the transponder was installed by that manufacturer.

[Doc. No. 18334, 54 FR 34311, Aug. 18, 1989, as amended by Amdt. 91–267, 66 FR 21066, Apr. 27, 2001]

EFFECTIVE DATE NOTE: At 66 FR 41116, Aug. 6, 2001, $\S91.413$ was amended by removing paragraph (c)(1)(iv), effective Apr. 6, 2003.

§91.415 Changes to aircraft inspection programs.

- (a) Whenever the Administrator finds that revisions to an approved aircraft inspection program under §91.409(f)(4) are necessary for the continued adequacy of the program, the owner or operator shall, after notification by the Administrator, make any changes in the program found to be necessary by the Administrator.
- (b) The owner or operator may petition the Administrator to reconsider the notice to make any changes in a program in accordance with paragraph (a) of this section.
- (c) The petition must be filed with the FAA Flight Standards district office which requested the change to the program within 30 days after the certificate holder receives the notice.
- (d) Except in the case of an emergency requiring immediate action in the interest of safety, the filing of the petition stays the notice pending a decision by the Administrator.

§91.417 Maintenance records.

- (a) Except for work performed in accordance with §§ 91.411 and 91.413, each registered owner or operator shall keep the following records for the periods specified in paragraph (b) of this section:
- (1) Records of the maintenance, preventive maintenance, and alteration and records of the 100-hour, annual, progressive, and other required or approved inspections, as appropriate, for each aircraft (including the airframe) and each engine, propeller, rotor, and appliance of an aircraft. The records must include—
- (i) A description (or reference to data acceptable to the Administrator) of the work performed; and